



200.33233C6

SPINA MOBILE

IP44 32A 3P+N+T+2piloti 400V GRIGIO
 CRIMP. 6mm² Tipo 3C 3P+N+T 32A 400V~
 22kW

Certificati

TECHDATA		NORME E LEGGI	
Tipo installazione	PORTATILE	EN 62196-1 (2014)	[European Standard] Plugs, socket-outlets and vehicle couplers. Conductive charging of electric vehicles. Part 1: Charging of electric vehicles up to 250 A a.c. and 400 A d.c.
Serie commerciale	Serie LIBERA		
Tipologia prodotto	SPINA MOBILE	EN 62196-2 (2017)	[European Standard] Plugs, socket-outlets and vehicle couplers. Conductive charging of electric vehicles. Part 2: Dimensional interchangeability requirements for a.c. pin and contact-tube accessories
Descrizione sintetica	SPINA MOBILE		
Grado di protezione IP	IP44	DIRETTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Corrente nominale	32A		
Poli	3P+N+T+2piloti		
Tensione nominale	400V		
Colore	GRIGIO		
Materiale	TERMOPLASTICO		
Note	CRIMP. 6mm ²		
EV standard	Tipo 3C 3P+N+T 32A 400V~ 22kW		