

SPECIFICHE

CAMERA

Sensore di immagine: 1/2.8" Progressive Scan CMOS Starlight Sensor

Lenti: Focal Length: 3.17 mm

Aperture: F1.65

Field of View: 125° (Diagonal), 111°(Horizontal), 56°(Vertical)

Si: 850 nm IR LED (30 ft / 9.1 m)

Full-Color Night Vision

Lighting: 2× Spotlights

Interface & Button : 1× POWER Button

1× RESET Button

1× MicroSD Card Slot (Up to 512GB)

SOLAR PANEL

Connection Capacity: A solar panel can only connect to one camera.

Output Port: Type-C

VIDEO & AUDIO

Maximum Resolution: 2K 3MP (2304 × 1296 px)

Frame Rate: 15 fps

Video Compression: H.264

Live View: Yes

Image Enhancement: 3DNR

WDR

Audio Input & Output: Built-in Microphone and Speaker

Audio Communication: Two-Way Audio with Noise Cancellation

Siren Volume: 94 dB (Level measured at 4-inch/10-cm distance)

STORAGE

Local Storage: MicroSD Card Slot on Camera (Up to 512 GB)

Cloud Storage: Tapo Care Cloud Storage Services (Subscription required)

DETECTION and NOTIFICATIONS

Sensor: Single Motion Sensor (FOV: 110° horizontal)

Single Ambient Light Sensors

AI Detection: Motion Detection

Person Detection

Activity Zones: Yes

Output Notification : System Notification

System Notification with Snapshot (Tapo Care Services)

NETWORK

Network Connectivity: Connect via Wi-Fi

Wireless Connectivity: IEEE 802.11b/g/n, 2.4 GHz Wi-Fi

SECURITY

128-bit AES Encryption with SSL/TLS

WPA/WPA2-PSK

POWER

Power Source: Built-in Rechargeable Lithium-ion Battery

Solar Panel: Tapo A201

Input Voltage: Adapter Input: 100-240 V, 50/60 Hz

Output Voltage: Adapter Output: 5.0 V, 1.0 A

Solar Panel Max Charging Voltage: 5.2 V

Solar Panel Max Charging Power: 2.5 W

GENERALE

Smart Integration: Google Assistant, Amazon Alexa

Weather Resistance: IP65

System Requirements : Tapo App: iOS 11.0 or higher, Andriod 5.0 or higher

Mounting Options: Tabletop

Ceiling-Mounted

Wall-Mounted

Operating Temperature: -20°C~45°C

Storage Temperature: -20°C~60°C

Operating Humidity: 10%~90% RH, Non-condensing

Storage Humidity: 5%~90% RH, Non-condensing

Charging Temperature: 0-45°C

Dimensions: Camera Dimensions: D60mm × 89mm

Solar Panel Dimensions: 173.42 × 120.42 × 15.7 mm (6.83 × 4.74 × 0.62 in)

Contenuto della confezione: TC82 Camera ×1

Tapo A201 Solar Panel ×1

Tapo A201 Solar Panel Bracket ×1

USB Adapter Cable ×1

Base Cover ×1

Extension Wire ×1

Mounting Screws ×6

Mounting Anchors ×6

Waterproof Seals ×2

Screw Caps ×2

Cable Zip Tie ×1

Mounting Templates ×2

Quick Start Guide

Certifications: CE, FCC, DOE, CEC, RCM, KC, NCC, BSMI, NTRA, IP65

[Prodotti](#)

[Supporto](#)

[Chi Siamo](#)

[Download App](#)

[Tapo Footer List](#)

[Sicurezza](#)

[Supporto](#)

[Chi Siamo](#)

[Informativa Privacy](#)