



# CorePro LED linear MV



# CorePro LEDlinearND 11.5-100W R7S78mm830

CorePro R7S is a retrofit replacement for traditional double-ended linear R7S lamps. Its 'light all around' design delivers light just like a halogen lamp. Within the range you can choose dimmable products which have deep dimming function that enables a cozy ambience when using a dimmable fixture.

#### **Product data**

General Information	
Cap-Base	R7s
Nominal lifetime	15,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
Warranty period	2 years
Light Technical	
Color Code	830 [CCT of 3000K]
Beam Angle (Nom)	300 degree(s)
Luminous Flux	1,521 lm
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	132 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Photobiological safety according to EN 62471	RG0

Operating and Electrical	
Input Frequency	50 to 60 Hz
Power Consumption	11.5 W
Lamp Current (Nom)	80 mA
Wattage Equivalent	100 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.5
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	104 °C
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Clear
Bulb Material	Clear Plastic
Bulb Shape	R7S


Datasheet, 2025, September 27 data subject to change

# CorePro LED linear MV

Net Weight (Piece)	0.065 kg
Approval and Application	
Energy Efficiency Class	E
Suitable For Accent Lighting	No
Energy Consumption kWh/1000 h	12 kWh
EPREL Registration Number	1880096
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes
Flickering value (PstLM) - Flickering value as pe	er 1
EN 61000-3-3	
Stroboscopic effect visibility measure (SVM)	0.4
Ambient temperature range	-20 to +45 °C
Application Conditions	
can it be used in closed luminaires	No


Product Data	
Order product name	CorePro LEDlinearND 11.5-100W
	R7S78mm830
Full product name	CorePro LEDlinearND 11.5-100W
	R7S78mm830
Full product code	872016930199300
Order code	929003791502
Material Nr. (12NC)	929003791502
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169301993
Numerator - Packs per outer box	10
EAN/UPC - Case	8720169302006

### Dimensional drawing



Product	D	С
CorePro LEDlinearND 11.5-100W R7S78mm830	28 mm	78 mm

#### Photometric data






Spectral Power Distribution Colour - CorePro LEDlinearND 11.5-100W R7S78mm830

General uniform lighting - CorePro LEDlinearND 11.5-100W R7S78mm830


# CorePro LED linear MV


#### Photometric data



Light Distribution Diagram - CorePro LEDlinearND 11.5-100W R7S78mm830

### Lifetime





Life Expectancy Diagram

Lumen Maintenance Diagram - CorePro LEDlinearND 11.5-100W R7578mm830



© 2025 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.