



# MASTER VALUE LED spot MV



## MAS LED spot VLE D 3.7-50W GU10 940 60D

MASTER Value, LED, PAR16, Only with specific dimmers, GU10, 4000 K, 370 lm, CRI 90, 25000 hour(s), Glass

Delivering a warm, halogen-like accent beam, MASTER VALUE is a perfect fit for spot lighting. Thanks to its high CRI, it realizes more natural colors, creating cozy and comfortable ambiances for residential and hospitality projects, and emphasizing the beauty of merchandise in retail. These LED spots MV GU10 have the familiar look and feel of spot lamps, keeping the classic beauty of glass spots and adding the strong performance of LED technology. The dimming function enables you to create the atmosphere you desire, and it works with broad selection of dimmers. MASTER VALUE also offers more energy savings than normal LED spots.

### Warnings and Safety

- Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights

### Product data

General Information		Warranty period	
Cap-Base	GU10	5 years	
Nominal lifetime	25,000 hour(s)	Light Technical	
Switching Cycle	25,000	Color Code	940 [CCT of 4000K]
Lighting Technology	LED	Beam Angle (Nom)	60 degree(s)
Flux measurement reference	Narrow Cone	Luminous Flux	370 lm
		Luminous Intensity (Nom)	420 cd

# MASTER VALUE LED spot MV

Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	100 lm/W
Color Consistency	<6
Color rendering index (CRI)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %
Luminous Flux in 90° Cone (Rated)	370 lm
Photobiological safety according to EN 62471	RG1

## Operating and Electrical

Input Frequency	50 to 60 Hz
Power Consumption	3.7 W
Lamp Current (Nom)	27 mA
Wattage Equivalent	50 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.6
Voltage (Nom)	220-240 V

## Temperature

T-Case Maximum (Nom)	62 °C
----------------------	-------

## Controls and Dimming

Dimmable	Only with specific dimmers
----------	----------------------------

## Mechanical and Housing

Bulb Finish	Clear
Bulb Material	Glass
Bulb Shape	PAR16
Net Weight (Piece)	0.041 kg

## Approval and Application

Energy Efficiency Class	E
Suitable For Accent Lighting	Yes
Energy Consumption kWh/1000 h	4 kWh
EPREL Registration Number	2150479
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	0.4
Ambient temperature range	-20 to +45 °C


## Application Conditions

can it be used in closed luminaires	No
-------------------------------------	----

## Product Data

Order product name	MAS LED spot VLE D 3.7-50W GU10 940 60D
Full product name	MAS LED spot VLE D 3.7-50W GU10 940 60D
Full product code	872016939938900
Order code	929004248402
Material Nr. (12NC)	929004248402
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169399389
Numerator - Packs per outer box	10
EAN/UPC - Case	8720169399396


## Dimensional drawing




Product	D	C
MAS LED spot VLE D 3.7-50W GU10 940 60D	50 mm	54 mm

MASTER VALUE LED spot MV


Photometric data



Light Distribution Diagram - MAS LED spot VLE D 3.7-50W GU10 940 60D




Spectral Power Distribution Colour - MAS LED spot VLE D 3.7-50W GU10 940 60D




Source: Philips Lighting B.V. Page 10

Accent Lighting Spots - MAS LED spot VLE D 3.7-50W GU10 940 60D

Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram - MAS LED spot VLE D 3.7-50W GU10 940 60D

## MASTER VALUE LED spot MV

