

Interruttore crepuscolare da esterno


Twilight switch

Itaca-22



IP54

**-30°
+60°**



50-60 Hz - 230 Vac
Design innovativo
Installazione su parete o palo
Classe di protezione II
Scocca resistente a polvere e pioggia
Resistente ai raggi UV
Led di segnalazione istantanea del punto di taratura
Soglia di intervento: 2-200 Lux
Carico massimo relè: 16A - 250 Vac
Ritardo di intervento 7s circa

CR301ES unipolare
Ritardo spegnimento 30 secondi

CR302ES bipolare, interruzione di fase e neutro
Ritardo spegnimento 25 secondi

50-60 Hz - 230 Vac
Innovative design
Wall or pole mounting
Protection class II
Dust and rain proof case
UV-rays proof
Led for instant signalling of calibration point
Intervention threshold: 2-200 Lux
Max relay rating: 16A - 250 Vac
Switch on delay 7s

CR301ES single-pole
Switch off delay 30 second

CR302ES double-pole, phase and neutral interruption
Switch off delay 25 second

CODICE	INCANDESCENZA	ALOGENA	FLUORESCENZA	LED 230V	TIPO	PESO
CODE	INCANDESCENT	HALOGEN	FLUORESCENT	LED 230V	TYPE	WEIGHT
	W	W	W	W		gr
CR301ES	2300	2000	1100	300*	unipolare 1 NO 16A	100
CR302ES	2300	2000	1100	300*	bipolare 2 NO 16A	110

*Le potenze riportate sono indicative e dipendono dalla qualità e dalla tipologia del dispositivo LED 230V
LED 230V device power are just approximated and are connected to quality and typology of them