

ALTRO

Certificazione	FCC, CE, RoHS
Contenuto della confezione	PoE Splitter TL-POE10R Power Cord RJ45 Cable Installation Guide
Requisiti di sistema	Microsoft® Windows® 98SE, NT, 2000, XP, Vista™ or Windows 7, MAC® OS, NetWare®, UNIX® or Linux.
Ambiente	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

CARATTERISTICHE HARDWARE

Interfaccia	2 10/100/1000Mbps RJ45 Port AUTO Negotiation/AUTO MDI/MDIX 1 POWER OUTPUT PORT
Media	10BASE-T: UTP category 3, 4, 5 cable (Max 100m) EIA/TIA-568 100Ω STP (Max 100m) 100BASE-TX: UTP category 5, 5e cable (Max 100m) EIA/TIA-568 100Ω STP (Max 100m) 1000BASE-T: UTP category 5, 5e, 6 cable (Max 100m)
Alimentazione	12VDC 1A, 9VDC 1A, 5VDC 2A
Utilizzo principale	Compatible With IEEE 802.3af Compliant PSEs Delivers Power Up To 100 Meters Optional 12VDC, 9VDC or 5VDC Power Output
LED	PWR
Dimensioni (L x P x A)	3.2*2.1*0.9 in. (80.8*54*24 mm)

CARATTERISTICHE SOFTWARE

Funzionalità di base	Compatible With IEEE 802.3af Compliant PSEs Delivers Power Up To 100 Meters Optional 12VDC, 9VDC or 5VDC Power Supply
----------------------	---