

## PRODUCT DATASHEET

### NIGHTLUX Hall White

NIGHTLUX® Hall | Mobile nightlights with motion sensor and tilt function, battery-powered



#### Areas of application

- For a very large range of uses
- Indoor and outdoor
- Entrances / Hallways
- Corridors

#### Product benefits

- Attractive and functional design
- Economical operation due to low power consumption
- Easy and fast mounting on nearly every surface (adhesive tape or screws)
- Light direction individually adjustable
- Accessories for flexible mounting options included

#### Product features

- Integrated light and motion sensor
- Available in two housing colors
- Switch for Auto- or On/Off-Mode
- Type of protection: IP54



## TECHNICAL DATA

### Electrical data


Nominal wattage	0.25 W
Nominal voltage	4,5 V
Mains frequency	50...60 Hz
Nominal current	55.000 mA
Protection class	III
Operating mode	Battery

### Photometrical data

Luminous flux	14 lm
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	≤6 sdcn

### Dimensions & Weight

Length	195.00 mm
Width	140.00 mm
Height	25.00 mm
Product weight	98.00 g



### Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC)
Mercury content	0.0 mg

## Application & Mounting

Ambient temperature range	0...+25 °C
Temperature range at storage	-20...+50 °C
Type of protection	IP54
Dimmable	No
Mounting type	Surface
Application environment	Indoor
With light source	Yes
Replaceable light source	No

## Lifespan

Lifespan L70/B50 at 25 °C	25000 h <sup>1)</sup>
---------------------------	-----------------------

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## Sensor

Type of sensor	Motion
Sensor technology	Passive infrared (PIR)
Sensor detection angle	120 °
Sensor controlled switching time	20 s

## BATTERY

Type of Battery	Alkaline
Battery size [GMS]	AAA
Number of included batteries	3
Nominal voltage of battery	1.5 V

## Certificates & Standards

Standards	CE / UKCA / EAC
Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable



## EQUIPMENT / ACCESSORIES

– Batteries included: 3x1.5 V LR03 (AAA)

## Safety advice

- This product is not a toy. It should not be left unattended in the hands of children or operated by children.
- Not designed as a replacement for conventional lighting in private household.
- Battery Warning: Keep out of reach for children. Swallowing can lead to chemical burns, perforation of soft tissue, and death. Severe burns can occur within 2 hours of ingestion. Seek medical attention immediately.
- If the battery compartment (if applicable) does not close securely, stop using the product and keep it away from children. If you think batteries might have been swallowed or placed inside any part of the body, seek immediate medical attention.
- Please avoid: Maximal ambient temperature: +35 °C. Replacement of a battery with an incorrect type that can defeat safeguard (for example, in the case of some lithium battery types). Altitude during operation: 2000 m. Disposal of a battery into fire or a hot oven, or mechanically crushing or cutting of a battery, that can result in an explosion.

### DOWNLOAD DATA

Documents and certificates	Document name
 Legal information	Safety Insert DECOR HELPER AND NIGHTLUX
 Declarations of conformity	CE Declaration Nightlux Hall

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854530999	Blister 1	25 mm x 140 mm x 195 mm	118.00 g	0.68 dm <sup>3</sup>
4099854531002	Shipping box 6	163 mm x 154 mm x 210 mm	817.00 g	5.27 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.