

# PRODUCT DATASHEET

## 1906 Letter Table Bar 1.2W E27

Vintage 1906 Letter Table | Table luminaire, E27 socket



---

### Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, bedrooms, basements

---

### Product benefits

- Eye-catching lamp design with LEDs in neon colors
- Sustainable solution thanks to exchangeable light sources
- Inline-switch on the cable
- Osram lamp included

---

### Product features

- Housing material: metal and glass
- Textile cable

## TECHNICAL DATA

### Electrical data


Nominal wattage	1.2 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Inrush current	6 A
Inrush current time $T_{h50}$	100 $\mu$ s
Max. number of luminaires per miniature circuit breaker C10	91
Max. number of luminaires per miniature circuit breaker C16	146
Power factor $\lambda$	0.40
Protection class	II
Operating mode	Mains voltage

### Photometrical data

Luminous flux	100 lm
Total luminous flux of contained light sources	100
Luminous efficacy	83.3 lm/W
Color temperature	3000 K
Color rendering index Ra	70
Flickering metric (Pst LM)	<1
Photobiological safety group acc. to EN62778	RG1

### Dimensions & Weight

Diameter	125.00 mm
Height	231.00 mm
Product weight	305.00 g
Cable length	1800 mm



1906 LETTER TABLE

### Materials & Colors

Product color	Black
Housing color	Black
Body material	Steel

Glow Wire Test according to IEC 60695-2-12	650 °C
--	--------

### Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Plug type C (EU)
Type of protection	IP20
Dimmable	No
Mounting type	Standing
Mounting location	Table
Adjustable	No
With light source	Yes
Replaceable light source	Yes
Holder designation	E27

### Lifespan

Lifespan L70/B50 at 25 °C	15000 h <sup>1)</sup>
Number of switching cycles	10000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Certificates & Standards

Standards	CE
-----------	----



### Additional product data

Product remark	Maximum bulb wattage: 18 W LED / Available from September 2025
Number of illuminants	1

### Safety advice

- The external flexible cable or cord of this luminaire cannot be replaced; if the cord is damaged, the luminaire must be disposed of.
- To reduce the risk of strangulation the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm's reach.

### DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	1906 Table Letter
	Declarations of conformity	CE Declaration 1906 Table Letter Luminaires

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075853201	Folding box 1	137 mm x 137 mm x 273 mm	493.00 g	5.12 dm <sup>3</sup>
4058075853218	Shipping box 4	290 mm x 290 mm x 298 mm	2283.00 g	25.06 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.