



TL-SF1016D

Switch Desktop 10/100Mbps 16 Porte

CARATTERISTICHE HARDWARE

Interfaccia	1610/100Mbps RJ45 Ports AUTO Negotiation/AUTO MDI/MDIX
Numero ventole	Fanless
Physical security lock	No
Consumo energetico	Maximum: 3.1W (220V/50Hz)

CARATTERISTICHE HARDWARE

Alimentatore esterno	100~240VAC, 50/60Hz
Tabella ARP	1K
Dimensioni (L x P x A)	7.9*5.6*1.6 in. (200*142*40 mm)
Max. Power Consumption	3.23 W (220V/50Hz)
Max. Heat Dissipation	11.01 BTU/h

CARATTERISTICHE SOFTWARE

Caratteristiche avanzate	Green Technology, saving power up to 80% 802.3X Flow Control, Back Pressure
Metodo di trasmissione	Store and Forward

ALTRO

Certificazione	FCC, CE, RoHs
Contenuto della confezione	16-Port 10/100Mbps Desktop Switch TL-SF1016D Power Adapter User Guide
Requisiti di sistema	Microsoft® Windows® 98SE, NT, 2000, XP, Vista™ or Windows 7, MAC® OS, NetWare®, UNIX® or Linux.
Ambiente	Operating Temperature: 0°C~40°C (32°F~104°F); Storage Temperature: -40°C~70°C (-40°F~158°F); Operating Humidity: 10%~90% non-condensing; Storage Humidity: 5%~90% non-condensing

Iscriviti alla newsletter ⓘ

[Iscriviti](#)

Seguici



About

[Corporate Profile](#)[About Us](#)[Sustainability](#)[Contact Us](#)[Careers at TP-Link](#)[Privacy Policy](#)[Codice di buona condotta e reclami](#)

Press

[News](#)[Blog](#)[Security Advisory](#)

Dove Acquistare

[Distributori](#)

Partners

[Partner Program](#)

Learning Center

[Technology Trends](#)